

32" All-in-one Transparent Box Display with  
Built-in Speaker and content management software

2 Nos.

**Panel**

Screen Size	32"
Backlight/Lightsource	LED light bar
Active Area (horizontal × vertical)(mm)	697.7 x 392.3mm
Resolution (pixels)	1366 x 768
Brightness (typical)	250 nits
Contrast Ratio (typical)	3000:1
Viewing Angle (horizontal/vertical)	178° / 178°
Aspect Ratio	16:9
Light Life (typical)	30,000hrs
Display Orientation	Landscape

**Audio**

Internal Speaker (Amp)	2W + 2W
Audio Line In/Out (3.5mm)	x1 / No

**Connectivity**

VGA In/Out	x1 / No
DVI In/Out	x1 / No
HDMI In/Out	x1 / No
USB port (Type A)	x1 (2.0)

**Power**

AC/DC In	DC
Voltage	100V ~ 240V, 50Hz / 60Hz
Power Consumption (typical/standby)	90W / $\leq$ 0.5W

**Mechanical**

Dimension (WxHxD) (mm)	813.5 x 511.0 x 336.7 mm
Bezel Width (top/bottom/left/right) (mm)	19.0 / 48.8 / 16.7 / 16.7mm

**Environment**

Operation Temperature	0°C ~ 50°C
-----------------------	------------

Storage Temperature	-20°C ~ 60°C
Usage (Hour/Day)	24/7
<b>OSD</b>	
On-Screen Display Languages	English
<b>Software</b>	
Content creation and management	Yes
<b>Accessory</b>	
Remote Control	Yes
Power Cord (by region)	Yes
VGA Cable	Yes
User's Manual Electronic File	Yes
Warranty	OEM Standard

## 55" FHD Transparent Signage

2 Nos.

Resolution:	1,920 x 1,080 (FHD)
Transmittance:	10%
Screen Sizes	54.64" (1,387.80mm) diagonal
Technology	In-plane Switching
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080
Contrast Ratio	1,000 (Typ.) 1,300
Viewing Angle (H x V)	178 x 178
Response Time	9ms (G to G)
Anti-reflection treatment of the front polarizer	Reflectance < 2%
Guaranteed Operating Hour	24 Hours 24 Hours
Orientation	Portrait & Landscape
Connectivity	Input LVDS(1)
Operating Temperature Range	0°C to 40°C
Operating Humidity Range	10 % to 80 %
Warranty	OEM Standard