



**Note:-**

- 1) The entire structure is made of PVC Rigid Foam Sheet. (white) as mentioned in drawing.
- 2) Flash type service door should be provided with MS angle frame at back side and 3" good quality SS hinge with single key multipurpose lock.
- 3) T.W. Frame work for vertical (50 x 50, 50 x 25) & horizontal (50 x 25) respectively. PVC Rigid foam sheet to be fixed with adhesive.
- 4) Top surface to be covered with 10 mm thk PVC rigid foam sheet.
- 5) MS angle bracket for panel support to be fixed with wall on top and bottom surfaces.
- 6) Dimensions may vary as per site condition.
- 7) All welded joints of MS angle structure & MS frame work should be highly paint finished.
- 8) Acrylic Solid surface 6mm thk. white.
- 9) 19 mm thick BWR grade ply, IS-303
- 10) All dimensions are in mm.

(129 SQ. Mt.)

<b>NATIONAL COUNCIL OF SCIENCE MUSEUMS</b>	
<b>UNIT:</b> C.R.T.I.	<b>PROJ.:-</b> S.N.BOSE
<b>DRG. NO.</b> EX-LAY-04/06/18	<b>DATE</b> 24-04-18
<b>SCALE</b> 1 : 60	<b>TOLERANCE</b> ± 0.25mm
<b>TITLE:-</b> Gallery Layout of S.N. Bose, Museum	
<b>DRN. BY</b> <i>[Signature]</i>	<b>APPD. BY</b> <i>[Signature]</i>
<b>CKD. BY</b> <i>[Signature]</i>	<b>NO OFF.</b> <i>[Signature]</i>