

**Rear Projection Silver depolarizing Screen for passive stereoscopic dual head system
with detachable metallic Frame - 1 Set**

viewing area of screen: **12 feet x 9 feet**

Integrated polyester screen (without perforation) and high quality metallic frame system

Detailed specification

Screen material:

Flexible Rear projectionSilver 3D with uniform depolarizing coating

Stereoscopic, two channel passive dual head display

High gain coating: Minimum 3.0 Peak Gain at 0⁰; Half Gain at 24⁰

High Contrast Level

The screen should have black border

The screen material should be rollable, robust, washable and **Flame retardant**.

The packing of the screen should be tube rolled with protective passive spacer for the sensitive screen coating.

Should have certified operating life for at least 10 years

Screen Frame:

Snapper Deluxe Quicksnap type or equivalent

VeLux applique finish for absorbing projector over-scan.

Sturdy detachable metal frame for holding the screen for even and smooth stretching in all directions without any crease.

Overall frame Height should not be more than 10 ft.

around 3 1/2" aluminum extrusion frame with beveled edge for superior fit and finish.

Quick-snap fastening system for attaching screen to frame

The system should have provision for firm vertical mounting on the wall.

The system should be free of any manufacturing defect and patch on the screen. Screen material should be certified by the manufacturer for overall gain distribution.

Warranty: Minimum One year