

सामग्री का विवरण और विनिर्देश/ Description & Specification of Store	मात्रा/ Quantity
01. Phenol Bonded Plywood, C.P.Teak Wood Section, Rigid PVC Foam Sheet and Decorative Laminate Sheet strictly as per enclosed specification & Quantity mentioned in the Annexure.	

दर केवल एफ.ओ.आर बिधान नगर के आधार पर बतलाई जानी चाहिए।/ Rate should be quoted on F.O.R. Bidhannagar basis only.

वर्तमान जी.एस.टी की लागू दर (%) को स्पष्टतः दर्शाते हुए दर को उद्धृत किया जाना चाहिए एवं, निविदा के साथ जी.एस.टी पंजीयन प्रमाण पत्र की प्रति भी प्रस्तुत की जानी चाहिए। (अनंतिम पंजीयन प्रमाण पत्र भी कुछ वक्त के लिए इस उद्देश्य की पूर्ति करेगा)/ Rate should be quoted clearly indicating applicable rate (%) of present GST and also submit copy of GST Registration Certificate along with the tender. (Provisional Registration Certificate will also serve the purpose for the time being)

दर पूर्णतः प्रति खंड के आधार पर ही बताई जानी चाहिए। दर सूचियों में शीघ्रतम सुपुर्दगी का समय उल्लिखित किया जाना चाहिए।/ Rate should be quoted strictly per piece basis only. Earliest Delivery Period must be mentioned in the quotations.

मोहरबंद कोटेशन, इन्हें प्रस्तुत करने की नियत तिथि के अगले कार्य दिवस पर 4 बजे अपराह्न में खोले जाएंगे।/ Sealed quotations shall be opened at 4 pm on the very next day of the due date for submission of quotations.

परिषद द्वारा किसी भी कारण से कोई अग्रिम नहीं दिया जाएगा। भुगतान हमारे द्वारा वस्तुओं के संतोषजनक निरीक्षण एवं उनकी सही हालत में प्राप्ति के बाद ही आपके बोजक की प्राप्ति की तिथि से 30 दिनों के भीतर किया जाएगा।/ No Advance shall be made by the Council for any reason whatsoever. Payment shall only be released after safe receipt and satisfactory inspection of the items at this end and within 30 days from the date of receipt of your invoice.

(नमूना: कोटेशन के साथ प्रस्तुत किया जा सकता है।/ Sample may be submitted along with your quotation)

O/C

जोच/
ENQUIRY

दूरभाष: 2357-0850/9347/48

फैक्स: 091-033-2357-6008

राष्ट्रीय विज्ञान संग्रहालय परिषद/ NATIONAL COUNCIL OF SCIENCE MUSEUMS
(संस्कृति मंत्रालय के अंतर्गत/ Under Ministry of Culture)



भारत सरकार/ GOVT. OF INDIA

ब्लॉक-जीएन/BLOCK-GN, सेक्टर-५/ SECTOR-V, बिधाननगर/BIDHANNAGAR, कोलकाता/KOLKATA-700091

सेवा में/ To

PLEASE SEE REVERSE

संदर्भ सं./ Ref. No. I-18013/3//21(169)

दिनांक/ Date: 13.12.2021

शीघ्र जाक
SPEED POST

प्रिय महोदय/ Dear Sirs,

नीचे मुद्रित नियमों व शर्तों के अनुसार हाशिए में दी गई सामग्री के लिए कृपया दिनांक _____ या उससे पहले अधोहस्ताक्षरी को संबोधित दो प्रतियों में अपने कोटेशन हमारी संदर्भ संख्या व तिथि के विधिवत उपरिअंकनयुक्त मोहरबंद लिफाके में प्रस्तुत करें।

Kindly submit on or before **29.12.2021** your quotation in **DUPLICATE** in **SEALED COVER** addressed to the undersigned with our reference number and date **DULY SUPERSCRIBED ON THE COVER** for the stores noted in the margin subject to the terms and conditions printed below:

हमारी संदर्भ संख्या व तिथि के विधिवत उपरिअंकन के बिना एवं मोहरबंद लिफाके में प्रस्तुत न करने पर निविदा-प्रपत्र स्वीकार नहीं किए जाएंगे।/ Tender Form if not submitted in sealed cover with our Reference No. and date duly superscribed will not be entertained.

विशेष नोट/ SPECIAL NOTE: अपना कोटेशन भेजते समय कृपया निम्नलिखित बिन्दुओं का विशेष रूप से उल्लेख करें/ While forwarding your quotation please mention specifically the following :-

(i) गुणवत्ता व निमिति/ Quality and make (ii) सुपुर्दगी अवधि/ Delivery period (iii) बैंक विवरण/ Bank details (iv) सुपुर्दगी या अन्य प्रभार, यदि कोई है, तो कोटेशन में अनिवार्यतः उल्लिखित हो, अन्यथा इसपर बाद में विचार नहीं किया जाएगा।/ Delivery or other charges, if any, must be mentioned in the quotation, otherwise this will not be considered later on.

यदि वस्तु/वस्तुओं का/के क्रयदेश दिया जाता है/दिए जाते हैं तो संग्रहालय के परिसर में सुपुर्दगी की जानी है। इसलिए संग्रहालय को शुल्क-मुक्त सुपुर्दगी किए जाने के आधार पर कोटेशन प्रस्तुत किया जाना चाहिए।/ The item(s) if ordered is/are to be delivered at the premises of the Museum. The quotation should, therefore, be submitted on the basis of delivery free to the Museums.

भवदीय/ Yours faithfully,


(K. Unnikrishnan)

Controller of Stores & Purchase

Annexure

S. No.	Materials with specification		Quantity																																																								
	Name of the Item	Specifications																																																									
1.	Phenol bonded Plywood Make: Century/ Equivalent	2440 mm x 1220 mm x 12 mm Thickness BWR-Quality IS:303	30 Nos.																																																								
2.	C.P. Teak Wood Section	25 mm x 50 mm x 2440 mm length 50 mm x 50 mm x 2440 mm length • Well season wood ,without sap ,knot and bend • Dimension mentioned is after planning	55 Nos. 40 Nos.																																																								
3.	Rigid PVC Foam Sheet	<p>2440 mm x 1220 mm x 6 mm thickness Colour: Grey</p> <p>2440 mm x 1220 mm x 6 mm thick Colour: White</p> <p>Surface Finish: Matt finish with hard surface coating</p> <ul style="list-style-type: none"> • Each sheet to be supplied with both side plastic cover protection for scratch resistant. • To be supplied without any scratches and broken edges. <table border="1"> <thead> <tr> <th colspan="4">Mechanical</th> </tr> </thead> <tbody> <tr> <td>Tensile Strength</td> <td>Mpa</td> <td>DIN 53455</td> <td>≥15</td> </tr> <tr> <td>Elongation at break</td> <td>%</td> <td>DIN 53455</td> <td>≥15</td> </tr> <tr> <td>Modulus of Elasticity</td> <td>Mpa</td> <td>DIN 53457</td> <td>900-1500</td> </tr> <tr> <td>Impact Strength</td> <td>KJ/m²</td> <td>ISO 179</td> <td>≥9.0</td> </tr> <tr> <th colspan="4">Physical</th> </tr> <tr> <td>Density</td> <td>g/cc</td> <td>DIN 53479</td> <td>0.5 to 0.6</td> </tr> <tr> <td>Hardness</td> <td>Shore D</td> <td>ASTM D 2240</td> <td>≥55</td> </tr> <tr> <td>Water Absorption</td> <td>%</td> <td>DIN 53495</td> <td>≥1.0</td> </tr> <tr> <td>Flammability</td> <td></td> <td></td> <td>Self-Extinguishing</td> </tr> <tr> <th colspan="4">Thermal</th> </tr> <tr> <td>Vicat Softening</td> <td>°C</td> <td>DIN 53460</td> <td>≥73</td> </tr> <tr> <th colspan="4">Electrical</th> </tr> <tr> <td>Dielectric Strength</td> <td>KV/cm</td> <td>DIN 53481</td> <td>≥90</td> </tr> </tbody> </table> <p><u>Salient Features</u> Weather proof</p>	Mechanical				Tensile Strength	Mpa	DIN 53455	≥15	Elongation at break	%	DIN 53455	≥15	Modulus of Elasticity	Mpa	DIN 53457	900-1500	Impact Strength	KJ/m ²	ISO 179	≥9.0	Physical				Density	g/cc	DIN 53479	0.5 to 0.6	Hardness	Shore D	ASTM D 2240	≥55	Water Absorption	%	DIN 53495	≥1.0	Flammability			Self-Extinguishing	Thermal				Vicat Softening	°C	DIN 53460	≥73	Electrical				Dielectric Strength	KV/cm	DIN 53481	≥90	35 Nos. 35 Nos.
Mechanical																																																											
Tensile Strength	Mpa	DIN 53455	≥15																																																								
Elongation at break	%	DIN 53455	≥15																																																								
Modulus of Elasticity	Mpa	DIN 53457	900-1500																																																								
Impact Strength	KJ/m ²	ISO 179	≥9.0																																																								
Physical																																																											
Density	g/cc	DIN 53479	0.5 to 0.6																																																								
Hardness	Shore D	ASTM D 2240	≥55																																																								
Water Absorption	%	DIN 53495	≥1.0																																																								
Flammability			Self-Extinguishing																																																								
Thermal																																																											
Vicat Softening	°C	DIN 53460	≥73																																																								
Electrical																																																											
Dielectric Strength	KV/cm	DIN 53481	≥90																																																								



		Resistance to chemical, water, termite etc. Excellent sound, thermal and electrical insulation Light weight, high flexural strength and impact resistance Decorative and fast colour Fire retardant Maintenance free Dimensionally stable - does not warp or swell Superior finish on both sides Economic and space saving material Easy bonding with any material as well as with itself Easy fabrication Outstanding printability																																			
4.	Decorated laminated sheet Make: Century/ Equivalent	2440mmx1220x1mm thickness <table border="1"> <thead> <tr> <th rowspan="2">Colour</th> <th colspan="2">Shade No.</th> </tr> <tr> <th>Century</th> <th>Greenlam</th> </tr> </thead> <tbody> <tr> <td>Deep blue</td> <td>247</td> <td>291</td> </tr> <tr> <td>Brown</td> <td>174</td> <td>181</td> </tr> <tr> <td>Yellow</td> <td>206</td> <td>207</td> </tr> <tr> <td>Red</td> <td>194</td> <td>203</td> </tr> </tbody> </table> without any scratches cutting marks and broken edges and supplied with both side cover protection	Colour	Shade No.		Century	Greenlam	Deep blue	247	291	Brown	174	181	Yellow	206	207	Red	194	203	10 Nos. 10 Nos. 10 Nos. 10 Nos.																	
Colour	Shade No.																																				
	Century	Greenlam																																			
Deep blue	247	291																																			
Brown	174	181																																			
Yellow	206	207																																			
Red	194	203																																			
		<table border="1"> <thead> <tr> <th>Properties</th> <th>Specified as per IS:2046-1995</th> </tr> </thead> <tbody> <tr> <td>Thickness</td> <td>1.0 mm (± 10%)</td> </tr> <tr> <td>Resistance to surface wear</td> <td>≥ 350 (revolutions)</td> </tr> <tr> <td>Resistance to immersion in boiling water</td> <td></td> </tr> <tr> <td>Mass increase (%)</td> <td>10.0% (Max)</td> </tr> <tr> <td>Thickness increase (%)</td> <td>11.8% (Max)</td> </tr> <tr> <td>Resistance to dry heat at 180°C</td> <td>Should pass test</td> </tr> <tr> <td>Dimensional stability at deviated temperature</td> <td></td> </tr> <tr> <td>Longitudinal (%)</td> <td>0.55% (Max)</td> </tr> <tr> <td>Transverse (%)</td> <td>1.025% (Max)</td> </tr> <tr> <td>Dimensional stability at 20⁰ C</td> <td></td> </tr> <tr> <td>Longitudinal (%)</td> <td>0.375% (Max)</td> </tr> <tr> <td>Transverse (%)</td> <td>0.60% (Max)</td> </tr> <tr> <td>Resistance to colour change</td> <td>Wool standard</td> </tr> <tr> <td>1. In Xenon ARC light</td> <td>Should pass test</td> </tr> <tr> <td>2. In Enclosed Carbon ARC light</td> <td>Should pass test</td> </tr> <tr> <td>Specific gravity gm/c.m3</td> <td>1.36 (Min)</td> </tr> </tbody> </table>	Properties	Specified as per IS:2046-1995	Thickness	1.0 mm (± 10%)	Resistance to surface wear	≥ 350 (revolutions)	Resistance to immersion in boiling water		Mass increase (%)	10.0% (Max)	Thickness increase (%)	11.8% (Max)	Resistance to dry heat at 180°C	Should pass test	Dimensional stability at deviated temperature		Longitudinal (%)	0.55% (Max)	Transverse (%)	1.025% (Max)	Dimensional stability at 20 ⁰ C		Longitudinal (%)	0.375% (Max)	Transverse (%)	0.60% (Max)	Resistance to colour change	Wool standard	1. In Xenon ARC light	Should pass test	2. In Enclosed Carbon ARC light	Should pass test	Specific gravity gm/c.m3	1.36 (Min)	
Properties	Specified as per IS:2046-1995																																				
Thickness	1.0 mm (± 10%)																																				
Resistance to surface wear	≥ 350 (revolutions)																																				
Resistance to immersion in boiling water																																					
Mass increase (%)	10.0% (Max)																																				
Thickness increase (%)	11.8% (Max)																																				
Resistance to dry heat at 180°C	Should pass test																																				
Dimensional stability at deviated temperature																																					
Longitudinal (%)	0.55% (Max)																																				
Transverse (%)	1.025% (Max)																																				
Dimensional stability at 20 ⁰ C																																					
Longitudinal (%)	0.375% (Max)																																				
Transverse (%)	0.60% (Max)																																				
Resistance to colour change	Wool standard																																				
1. In Xenon ARC light	Should pass test																																				
2. In Enclosed Carbon ARC light	Should pass test																																				
Specific gravity gm/c.m3	1.36 (Min)																																				

